

Plugging bar

Just Fit!



Lineup expanded! ($\phi 2.2$ to $\phi 20.0$)

IP67

※when sealing holes



Model change
NEW

RoHS2

Oilproof

Weather-proof

Actual size

For filling cable insertion opening

Anti falling lib

Prevents falling from rubber bushing



Displayed diameter


Easily identifiable applicable hole diameter. (excl. BB-022S)



Just fit for CAPCON, QUICK CAP, and JOIBOX !



■ Model / Specification / Size



【Common specification】

Working temp. : -25 to +80°C

Color : Black

Q'ty per package : 10 pcs/package

Material : Nylon 66 (Flammability:UL94V-2)

Model	Applicable hole dia.	Dimension (mm)				Weight	Model	Applicable hole dia.	Dimension (mm)				Weight
		A	B	L1	L2				A	B	L1	L2	
BB-022S	φ 2.2	2.2	3	16	1	0.5g	BB-100S	φ 10.0	10	11.5	21.5	1.5	2.0g
BB-025S	φ 2.5	2.5	3.5				BB-110S	φ 11.0	11	12.5			
BB-030S	φ 3.0	3	4				BB-115S	φ 11.5	11.5	13			
BB-033S	φ 3.3	3.3	4.3				BB-120S	φ 12.0	12	13.5			
BB-040S	φ 4.0	4	5				BB-130S	φ 13.0	13	14.5			
BB-050S	φ 5.0	5	6				BB-140S	φ 14.0	14	15.5			
BB-060S	φ 6.0	6	7	18	1	1.0g	BB-150S	φ 15.0	15	17	27	2	3.0g
BB-070S	φ 7.0	7	8				BB-160S	φ 16.0	16	18			
BB-080S	φ 8.0	8	9.5				BB-190S	φ 19.0	19	21			
BB-090S	φ 9.0	9	10.5	21.5	1.5	2.0g	BB-200S	φ 20.0	20	22			4.0g

■ Applicable products (as of Sep.,2021) Below table shows representative models (Product body color : Black,oilproof). Other product body colors also respond weatherproof.

hole dia.	Model	Rubber bushing	CAPCON (OA-W)						QUICK CAP (QW)	JOIBOX (JB)
			Wide range	Standard	Multiple	Slit	Long-bodied	Metallic slim		
φ 2.2	BB-022S	G08-224			OA-W16-224					
φ 2.5	BB-025S						OA-WS04M-20/25			
φ 3.0	BB-030S	G15M-302			OA-W15M-302				JB-WST303(accessory)	
φ 3.3	BB-033S	G11-334 G13-334			OA-W16-334	OA-W16-0334RS		OA-QWL09334S-4 OA-QW09334SRSN / OA-QW11334SRSN	JB-WST306	
φ 4.0	BB-040S	G15M-04 G11-402 G13-404		OA-W15M-04	OA-W16-402 OA-W16-404	OA-W16-0404RS		OA-WS06M-25/40 OA-QWL09404S-4 OA-QW09404SRSN / OA-QW11404SRSN	JB-W305 / JB-W307 / JB-W311 JB-WST303(accessory) / JB-WST304 JB-W303(accessory) / JB-W304 JB-W44(accessory)	
φ 5.0	BB-050S	G15M-05 G13-503		OA-W15M-05	OA-W16-503	OA-W16-0503RS		OA-WS07M-35/50	JB-WST303 JB-W303 / JB-W307	
φ 6.0	BB-060S	G08-06 G11-09※ G13-09※ G13-09B G13-602 G22-604		OA-W1606	OA-W16-602 OA-W22-604	OA-W16-0901RS※ OA-W22-0604RS		OA-WS08M-45/60 OA-QW09S※ / OA-QW0911S※ OA-QW09S-2※ / OA-QW0911S-2※ OA-QW09S-3※ / OA-QW0911S-3※ OA-QW0913S-3※ / OA-QWL09S-4※ OA-QWL0911S-4※ / OA-QWL0913S-4※ OA-QWL09334S-4※ / OA-QWL09404S-4※ OA-QW09SN※ / OA-QW0911SN※ OA-QW0913SN※ / OA-QWL09SN※ OA-QWL0911SN※ / OA-QWL0913SN※ OA-QW09SRSN※ / OA-QW0911SRSN※ OA-QW09334SRSN※ / OA-QW09404SRSN※ OA-QWH16-08SRSN※	JB-WST304(accessory)※ JB-WST306(accessory)※ JB-W304(accessory)※ JB-W44※	
φ 7.0	BB-070S	G15M-07 G22-704		OA-W15M-07	OA-W22-704			OA-WS09M-55/70	JB-WST303 JB-W303 / JB-W307 JB-W3028070	
φ 8.0	BB-080S	G08-08		OA-W1608		OA-W22-0801RS		OA-WS10M-65/80 OA-QW22-0801SRSN		
φ 9.0	BB-090S	G11-09A G13-09A		OA-W1609				OA-W1609-13L	JB-W305 / JB-W307(accessory) JB-W311(accessory) JB-WST304 / JB-WST306 JB-W304 JB-W44(accessory) JB-W3034070/JB-W3049070	
φ 10.0	BB-100S							OA-WS12M-80/100		
φ 11.0	BB-110S	G11-11 G22-16※ G22-16B		OA-W1611					OA-QW11S / OA-QW0911S OA-QW11S-2 / OA-QW0911S-2 OA-QW16S※ / OA-QW1619S※ OA-QW16SN※ / OA-QW1619SN※	JB-WST306
φ 11.5	BB-115S	G13-11				OA-W16-1151RS		OA-W1611-13L	OA-QW11S-3 / OA-QW0911S-3 OA-QW1113S-3 / OA-QWL11S-4 OA-QWL0911S-4 / OA-QWL1113S-4 OA-QW11SN / OA-QW0911SN OA-QW1113SN / OA-QWL11SN OA-QWL0911SN / OA-QWL1113SN OA-QW11SRSN / OA-QW0911SRSN OA-QW11334SRSN / OA-QW11404SRSN	JB-W305(accessory) / JB-W307 JB-W311 / JB-W44(accessory)
φ 12.0	BB-120S			OA-WW16-04/12 OA-WW20M-04/12						
φ 13.0	BB-130S	G13-13		OA-W1613 OA-W2213		OA-W16-1301RS		OA-W1613-13L	OA-QW13S-3 / OA-QW0913S-3 OA-QW1113S-3 / OA-QWL13S-4 OA-QWL0913S-4 / OA-QWL1113S-4 OA-QW13SN / OA-QW0913SN OA-QW1113SN / OA-QWL13SN OA-QWL0913SN / OA-QWL1113SN	JB-W311(accessory) JB-W44
φ 14.0	BB-140S	G13-14		OA-W1614				OA-W1614-13L		
φ 15.0	BB-150S			OA-WW16-08/15 OA-WW20M-08/15						
φ 16.0	BB-160S	G22-16A		OA-W2216						
φ 19.0	BB-190S	G22-19		OA-W2219					OA-QW19S / OA-QW1619S OA-QW19SN / OA-QW1619SN	
φ 20.0	BB-200S			OA-WW22-11/20 OA-WW25M-11/19						

※Products set to insert rubber bushing B. Follow the rubber bushing B's hole diameter.

【Cautions】 • CAPCON Metallic slim type interfere with anti falling lib but this does not affect product performance.

• Due to aging, cables of max. applicable diameter for each product may not be able to pass through after plugging bar is removed.

• Please consult us for models not listed on the table.



7000-21, Nakagawa, Hosoe, Kita-ku, Hamamatsu, Shizuoka 431-1304, Japan

TEL +81-53-522-5562 FAX +81-53-523-2362 e-mail : info@ohm.co.jp

URL : <https://www.ohm.jp/>

The contents of this catalog are subject to change for product improvement.
Colors of products may slightly differ from actual due to printing.